

Please enter the Preliminary Amendment prior to examination and before calculating filing fees. A clean copy of the claims as amended is provided for the convenience of the examiner. ✓

Respectfully submitted,

Date: 1/18/02

Richard A. Paikoff

Richard A. Paikoff
Registration No. 34,892
Duane Morris LLP
One Liberty Place
Philadelphia, PA 19103-7396
(215) 979-1853

Docket No: 283702-13 (D5053-00016)

2008 FEB 10 10:31 AM

VERSION WITH MARKINGS TO SHOW CHANGES MADE

1 (amended). An organic waste material treatment process for organic waste material received in a vessel comprising the steps of:

a) subjecting the contents of the vessel to conditions under which aerobic composting of the contents of the vessel will proceed in order to raise the temperature of the contents of the vessel to between 15-75°C to promote anaerobic digestion of the contents;

b) [a)] depleting oxygen [displacing air] in the vessel [and contents thereof with water] to create conditions suitable for anaerobic digestion of the contents to proceed;

c) adding an anaerobic bacterial inoculum to the contents of the vessel;

d) [b)] anaerobically digesting the contents of the vessel;

e) [c)] separating gaseous byproducts from residues resulting from step d) [b)];

f) [d)] removing at least a portion of residual water from the vessel;

g) [e)] evenly distributing [administering] air to the residues in the vessel to create conditions suitable for aerobic composting of the residues to proceed without agitating the contents of the vessel;

h) [f)] aerobically composting the residues by action of aerobic bacteria; and

i) [g)] recovering compost resulting from step h) [f)] from the vessel.

3 (amended). The organic waste material treatment process according to claim 1 [2], characterised in that the temperature of the contents of the vessel is raised to at least 50°C before commencement of step d) [a)].

6 (amended). The organic waste material treatment process according to claim 1 [4 or claim 5], characterised in that air is administered to the contents of the vessel before commencement of step a).

9 (amended). The organic waste material treatment process according to claim 7 [or claim 8], characterised in that air is administered to the contents of the vessel at about 25 kPa above atmospheric pressure.

10 (amended). The organic waste material treatment process according to claim 1 [any one of claims 2 to 9], characterised in that water is added to the contents of the vessel to adjust a moisture content of the contents of the vessel to between about 40 - 60 % wet weight (w/w) before commencement of step a).

13 (amended). The organic waste material treatment process according to claim 1 [11 or claim 12], characterised in that oxygen in the vessel is depleted at step b) by sealing the vessel and ceasing administration of air to the contents of the vessel, thereby providing no further oxygen reserves for aerobic bacteria therein, thus causing the aerobic bacteria to consume the oxygen remaining in the vessel.

17 (amended). The organic waste material treatment process according to claim 1 [any one of claims 1 to 16], characterised in that air is administered to the residues at step g) at a pressure of between 1-1000 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues in step e)].

18 (amended). The organic waste material treatment process according to claim 17, characterised in that air is administered to the residues at step g) at a pressure of between 5-50 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues].

19 (amended). The organic waste material treatment process according to claim 17 [or claim 18], characterised in that air is administered to the residues at step g) at a pressure of about 25 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues].

20 (amended). The organic waste material treatment process according to claim [any one of claims] 1 [to 19], characterised in that the portion of water removed from the vessel in step f) [d)] results in a moisture content of the residues of between 40 - 60 % wet weight (w/w).

21 (amended). The organic waste material treatment process according to claim [any one of claims] 1 [to 20], characterised in that the gaseous byproducts separated from the residues in step e) [c)] include methane.

22 (amended). The organic waste material treatment process according to claim [any one of claims] 1 [to 21], characterised in that the compost resulting from step h) [f)] has been aerobically stabilised.

23 (amended). An organic waste material treatment process for organic waste material received in a plurality of interconnected vessels comprising the steps of:

a) subjecting the contents of the or each vessel to conditions under which aerobic composting of contents will proceed in order to raise the temperature of the contents to between 15-75°C to promote anaerobic digestion of the contents;

b) depleting oxygen in the or each vessel to create conditions suitable for anaerobic digestion of the contents to proceed;

c) [a)] adding [displacing air in at least one of the vessels and contents thereof with] water received from an interconnected vessel to the or each vessel to create conditions suitable for anaerobic digestion of the contents to proceed in the or each vessel, whereby the contents of the interconnected vessel has [having] already undergone anaerobic digestion and the water contains an anaerobic bacterial inoculum;

d) [b)] anaerobically digesting the contents of the or each vessel;

e) [c)] separating gaseous byproducts from residues resulting from step d) [b)];

f) [d)] removing at least a portion of the water from the or each vessel and transferring the portion of the water to another interconnected vessel for use in step c) [a)];

g) [e)] evenly distributing [administering] air to the residues in the or each vessel to create conditions suitable for aerobic composting of the residues to proceed without agitating the contents of the vessel;

h) [f)] aerobically composting the residues; and

i) [g)] recovering compost resulting from step h) [f)] from the or each vessel.

25 (amended). The organic waste material treatment process according to claim 23 [24], characterised in that the temperature of the contents of the or each vessel is raised to at least 50°C before commencement of step d) [a)].

28 (amended). The organic waste material treatment process according to claim 23 [26 or claim 27], characterised in that air is administered to the contents of the or each vessel before commencement of step a).

31 (amended). The organic waste material treatment process according to claim 29 [or claim 30], characterised in that air is administered to the contents of the or each vessel at about 25 kPa above atmospheric pressure.

32 (amended). The organic waste material treatment process according to claim [any one of claims] 23 [to 31], characterised in that water is added to the contents of the or each vessel to adjust a moisture content of the contents of the or each vessel to between 40 - 60 % wet weight (w/w) before commencement of step a).

35 (amended). The organic waste material treatment process according to claim 23 [33 or claim 34], characterised in that oxygen in the or each vessel is depleted by sealing the or each vessel and ceasing administration of air to the contents of the or each vessel, thereby providing no further oxygen reserves for aerobic bacteria therein, thus causing the aerobic bacteria to consume the oxygen remaining in the or each vessel.

39 (amended). The organic waste material treatment process according to claim 23 [any one of claims 24 to 38], characterised in that air is administered to the residues at step g) at a pressure of between 1-1000 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues in step e)].

40 (amended). The organic waste material treatment process according to claim 39, characterised in that air is administered to the residues at step g) at a pressure of between 5-50 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues].

41 (amended). The organic waste material treatment process according to claim 39 [or claim 40], characterised in that air is administered to the residues at step g) at a pressure of about 25 kPa above atmospheric pressure to ensure even penetration of the residues by the air[, thereby facilitating aerobic composting of the residues].

42 (amended). The organic waste material treatment process according to claim 23 [any one of claims 24 to 41], characterised in that the portion of water removed from the or each vessel in step f) [d)] results in a moisture content of the residues of between 40 - 60 % wet weight (w/w).

43 (amended). The organic waste material treatment process according to claim 23 [any one of claims 24 to 42], characterised in that the gaseous byproducts separated from the residues in step e) [c)] include methane.

44 (amended). The organic waste material treatment process according to claim 23 [any one of claims 24 to 43], characterised in that the compost resulting from step h) [f)] has been aerobically stabilised.

45 (amended). A vessel for sequential anaerobic digestion and aerobic composting of organic waste material arranged, in use, to facilitate an organic waste treatment process as claimed in claim 1, comprising a means for receiving organic waste material, first feed means for supplying water to the vessel and second feed means for supplying air to the vessel, wherein the first and second feed means are arranged to evenly distribute water and air to the organic waste material; the vessel being devoid of any internal agitation means.

48 (amended). The vessel according to claim [any one of claims] 45 [to 47], characterised in that the vessel is provided with a gas extraction line to extract gases generated in the interior of the vessel during anaerobic digestion of the organic waste material or to extract surplus gases upon completion of aerobic composting of the organic waste material.

49 (amended). The vessel according to claim [any one of claims] 45 [to 48], characterised in that the vessel is constructed to withstand internal pressures of between about 1-1000 kPa above atmospheric pressure.

50 (amended). The vessel according to claim [any one of claims] 45 [to 49], characterised in that the second feed means supplies pressurised air to the vessel in a range of between about 1-1000 kPa above atmospheric pressure such that the pressurised air evenly penetrates the organic waste material.

52 (amended). The vessel according to claim 50 [or claim 51], characterised in that the second feed means supplies pressurised air to the vessel at about 25 kPa above atmospheric pressure.

53 (amended). The vessel according to claim [any one of claims] 45 [to 52], characterised in that the vessel is provided with a drainage means to remove at least a portion of water supplied to the vessel by the first feed means.

54 (amended). An apparatus arranged, in use, to facilitate an organic waste material treatment process as claimed in claim [any one of claims] 1 [to 44], comprising at least one vessel for sequential anaerobic digestion and aerobic composting of organic waste material as claimed in claim [any one of claims] 45 [to 53], a first recirculation means for recirculating gases extracted from the or each vessel to a first storage means, and a second recirculation means for recirculating water extracted from the or each vessel to a second storage means or an interconnected vessel, wherein the organic waste material in the interconnected vessel is undergoing anaerobic digestion.

56 (amended). The apparatus according to claim 54 [or claim 55], characterised in that the second storage means is a water storage tank for storing water extracted after anaerobic digestion of the organic waste material in the or each vessel.

59 (amended). The apparatus according to claim [any one of claims] 54 [to 58], characterised in that the first recirculation means is interconnected to a dewatering tank, the dewatering tank being arranged, in use, for removal of water from the extracted gases.

61 (amended). The apparatus according to claim [any one of claims] 54 [to 60], characterised in that the second storage means is provided with a heating means for heating water stored in the second storage means, the heating means being interconnected by the first recirculation means to the gas storage tank, such that, in use, methane gas stored in the gas storage tank is utilised by the heating means to transfer heat to the water stored in the second storage means.

62 (amended). The apparatus according to claim [any one of claims] 54 [to 61], characterised in that the first recirculation means is interconnected to a heat exchange means, the heat exchange means being arranged, in use, to facilitate transfer of heat energy from hot air extracted from the or each vessel, wherein the organic waste material in the or each vessel is undergoing aerobic composting.

Please delete claims 2, 4, 5, 11, 12, 14, 15, 16, 24, 26, 27, 33, 34, 36, 37 and 38, without prejudice.

PH1\916675.1